## **TECHNICAL DATA SHEET**



## RUST-OLEUM® STOPS RUST AUTOMOBILE PRIMER

Rust-Oleum® Stops Rust® Primers provide a sound base for application of Stops Rust® enamels on heavily rusted steel. Primers provide twice the rust prevention than using enamels alone. The use of primers promotes topcoat adhesion and helps prevent chipping, cracking and peeling. Use of Stops Rust primers eliminates the need for multiple coats of enamel finish. Not for use of galvanized steel.

- Provides a sound base coat for a smooth finish, prevents topcoats from soaking into the primed surface
- Ideal on interior / exterior use on bare or lightly rusted surfaces
- Alkyd formula that provides superior rust prevention, which provides lasting protection and beauty for projects
- Dries to the touch in 10 minutes can be recoated within 15-30 minutes
- · Fast-drying formula is wet sandable
- Topcoats should be tested in an inconspicuous area before beginning
- Coverage approximately up to 15 sq. ft. depending on surface porosity
- · Superior rust prevention which provides lasting protection and beauty for projects



Sub Brand

Color

Sheen

Base Type

Coating Material

Product Type

Container Size

Coverage Area

Tintable

Clean Up

Time Before Recoating

Cleanup

Recommended Surface

Indoor or Outdoor

Stain Blocking

Full Cure Time

Odorless

: Stops Rust

: Gray

: Flat

: Oil-Based

: Alkyd

: Primer

i iiiiic

: 12 oz.

: 10-12 sq. ft.

: No

: Mineral Spirits

: 30 min

: Xylene

: Metals

: Indoor and Outdoor

: No

: 4 hr.

: No

