



TECHNICAL DATA SHEET

Homax® Easy Patch Popcorn Ceiling Texture

Description

Homax® Knockdown Aerosol Wall Texture can also be used to apply this attractive decorative finish to an accent wall. Once applied, this heavy-bodied wall texture is knocked down using a drywall knife to achieve the finished look. Both professional contractors and DIYers can get the performance and results deserved with our popular aerosol texture products.

Details

Specially formulated for patching knockdown or “southwest style” drywall textures. Once applied, this premium-bodied texture is knocked down using a drywall knife to achieve the finished look. Can also be used to create decorative effects on accent walls or even texture an entire room.

- * Adjust to spray medium to heavy knockdown textures
- * Water-based formula
- * Low odor, easy clean up with water
- * Covers up to 60 sq. ft.
- * 20 oz.





Directions

Homax® Knockdown Texture is the fastest way to patch “knockdown” drywall textures. To achieve the best results, please read the following directions carefully before you begin your wall repair project.

VENTILATE AREA WELL. PROTECT SURROUNDING AREA FROM OVERSPRAY. DO NOT SPRAY ON CLOTHING, FURNITURE OR CARPET.

- * Water-based, use warm water for clean up.
- * Sprays best between 68°-72° F
- * Eye protection recommended

DIRECTIONS FOR USE:

MAKE ANY NECESSARY WALL REPAIRS BEFORE APPLYING. FOR BEST RESULTS, PRIME/SEAL AREA BEFORE AND AFTER APPLYING TEXTURE.

1. SHAKE CAN vigorously FOR ONE MINUTE prior to use.
2. TWIST OFF safety tab from nozzle.
3. Always practice spraying on cardboard or scrap drywall to determine preferred pattern.
Pointing away from face, adjust dial to desired pattern:
 - STRAIGHT UP for LIGHT KNOCKDOWN.
 - COUNTER CLOCKWISE for HEAVY KNOCKDOWN.
4. SPRAY using a circular motion. For a heavier knockdown pattern, spray in short bursts to build up texture. Shake can occasionally throughout use.
5. Allow texture to dry for 4 to 8 minutes, then knockdown. Use knockdown or 6-8” drywall knife, wet blade, hold nearly parallel to surface, and draw across texture applying little to no pressure. DRY TIME: Allow to dry 2-5 hours before painting (depending on heaviness of pattern).
6. TO STORE: To store, clear nozzle by turning can upside down and spraying until texture is cleared.



PRECAUTIONS AND FIRST AID:

Sanding and grinding dusts may be harmful if inhaled. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. The product may not be stable under certain conditions of storage or use: high temperature/pressure hazard. In a fire or if heated, a pressure increase will occur and the container may burst or explode. Keep away from heat, sparks and flame. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. Do not breathe vapor or mist. Do not swallow. Do not get on skin or clothing. Avoid contact with eyes. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a **POISON CENTER** or doctor/physician.

KEEP OUT OF THE REACH OF CHILDREN.