TECHNICAL DATA SHEET



Homax® Easy Patch Popcorn Ceiling Texture

Description

Homax® Easy Patch Popcorn Ceiling Texture is ideal for repairing or applying popcorn texture. Our new and improved actuator allows for easy vertical spraying of material. The water-based formula is dispensed in an aerosol, allowing you to easily make small repairs to damaged popcorn ceilings, plus it is easy to clean up. Low odor. One 14 oz. can covers up to 4 sq. ft.

Details

Popcorn ceiling repair can be a challenge for homeowners. Whether your ceiling texture is stained or damaged, blending in the new popcorn texture with the existing texture is critical to achieving a flawless, professional finish. Homax® makes it easier to create an invisible repair with our aerosol ceiling repair products.

Homax® Easy Patch Popcorn Ceiling Texture is ideal for repairing or applying popcorn texture. Our new and improved actuator allows for easy vertical spraying of material. The water-based formula is dispensed in an aerosol, allowing you to easily make small repairs to damaged popcorn ceilings.

- * Popcorn ceiling texture in a convenient aerosol
- * Vertical spray tip provides precision spray control
- * Water-based formula
- * Low odor, easy clean up with water
- * Covers up to 4 sq. ft.
- * 14 oz.

DIYers: No need to call in an expensive contractor. Homax gives you the power to repair your own popcorn ceiling texture.





Directions

Homax® Aerosol Ceiling Texture, Popcorn is the fastest way to patch damaged popcorn ceiling textures. To achieve the best results, please read the following directions carefully before you begin your textured ceiling repair project.

PROTECT WALLS AND SURROUNDING AREA FROM OVERSPRAY.

- * Water-based, use warm water for clean up.
- * Sprays best between 68°-72°
- * Eye protection recommended

DIRECTIONS FOR USE:

MAKE ANY NECESSARY CEILING REPAIRS BEFORE APPLYING. WATER DAMAGED OR STAINED AREAS SHOULD BE PRIMED / SEALED WHITE PRIOR TO USE.

- 1. Shake can vigorously for 1 minute.
- 2. Carefully insert straw into nozzle.
- 3. Hold can vertically approximately 10-14" from ceiling.
- 4. SPRAY using a sweeping (back and forth) motion.
- 5. To store: remove straw, turn can upside down and spray until texture is cleared.

DRY TIME:

Allow texture to dry 24 hours if painting is required.



DANGER! FLAMMABLE VAPOR. CONTENTS UNDER PRESSURE. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Contains Calcium Carbonate, Clay, Perlite, Titanium Dioxide and Dimethyl Ether (propellant). Vapors may catch fire. Keep away from heat, sparks and flame. Extinguish all flames and sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Store upright in a cool, dry place. Avoid prolonged exposure to sunlight and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Use with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with eyes and skin. Wear safety glasses or goggles. Wash hands after using.

FIRST AID:

For eye contact, flush thoroughly with water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. If inhaled, remove person to fresh air. If breathing does not improve, get medical attention.

KEEP OUT OF THE REACH OF CHILDREN.