

TECHNICAL DATA SHEET



METALLIC EMULSION

Crown Fashion For Walls Metallic Emulsion Paint allows you to bring a touch of glamour into your home.

AVAILABILITY

Colour Range	Sophistication, Dazzle, Refresh, Millioner, Striking, Vivid
Packaging	1.25L

PROPERTIES

Drying Time	1 - 2 hours surface dry Hard overnight
Finish	Metallic
Spreading Rate	15m ² per litre on smooth surfaces. Coverage is dependent on the kind of surface being painted and should be used as a guide only
Flash Point	Not applicable.
Limitations	For interior use only. Do not apply when air or substrate temperatures are likely to fall below 10°C or when the relative humidity is above 80% during application or the drying period.

PREPARATION

New Surfaces	All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Powdery, polished plaster or dense surfaces should be primed with Crown Trade Alkali Resisting Sealer.
Previously decorated surfaces	All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied e.g. dirt, grease etc. Remove all loose, failing or suspect paint. Feather edges of sound paint. Remove all dust. Organic growth must be removed and the areas treated with Crown Trade Fungicidal Solution. Fill any fixing holes, cracks and shallow surface defects using a suitable proprietary interior filler.

COATING SYSTEM

Apply two full coats of Crown Metallic Emulsion

APPLICATION

Stir well before use. Apply unthinned using a good quality paint brush or medium pile roller. Apply liberally. Do not exceed the recommended spreading rate.

CLEANING

Return surplus material to container. Wash with clean water immediately after use.

HEALTH AND SAFETY

Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Crown Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Paints products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.



P O Box 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG

Tel: 01254 704951 Fax: 01254 870155

Email: info@crownpaint.co.uk

Website: www.crownpaint.co.uk