

SUEDE TEXTURED EMULSION

Textured matt emulsion paint for walls and features. This paint gives walls a look of brushed suede.

Packaging 2.5 l

PROPERTIES

Drying Time

Under normal drying conditions touch dry in 2 hours, recoatable after 4 hours. Allow for adequate ventilation during the drying period.

Finish Textured

Composition

Pigment: Titanium Dioxide and inorganic extenders.
Binder: Vinyl acetate copolymer.
Solvent: Water.

Spreading Rate Depends on the surface

Flash Point Not applicable.

VOC Content Low

How to use

Open the tin and stir thoroughly. Paint on walls or ceilings evenly with a paintbrush using random multi-directional strokes to create a suede effect. For best results and even distribution of texture, apply a second coat.

PREPARATION

New Surfaces

All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Powdery, polished plaster or dense surfaces should be primed with Crown Trade Alkali Resisting Sealer. If painting onto new plaster or porous surfaces, we recommend sealing the surface with a coat of paint diluted with up to 40% of clean cold water. Don't apply in damp or humid conditions or in temperatures below 10°C.

Previously decorated surfaces

All surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied e.g. dirt, grease etc. Remove all loose, failing or suspect paint. Feather edges of sound paint. Remove all dust. Organic growth must be removed and the areas treated with Crown Trade Fungicidal Solution. Fill any fixing holes, cracks and shallow surface defects using a suitable proprietary interior filler. Patch prime bare and filled areas with Crown Suede Emulsion. Wash remaining sound paint with hot water and liquid detergent solution to remove any contaminants, frequently changing the water. Any glossy or eggshell surfaces should be wet abraded to provide a key. Rinse with clean water to remove all residues. Allow to dry. If after cleaning any areas still contaminated with substances likely to cause staining and/or bleeding, patch prime with one coat of Crown Stain Block Primer. Bring forward patch primed areas with one coat of Crown Suede Emulsion

COATING SYSTEM

Apply two full coats of Crown Suede Emulsion Breatheasy®.

APPLICATION

Stir well before use. Apply unthinned using a good quality paint brush or medium pile roller. Apply liberally. Do not exceed the recommended spreading rate.

CLEANING

Return surplus material to container. Wash with clean water immediately after use.

HEALTH AND SAFETY

Please refer to the Safety, Health and Environmental Information on the container. Take special precautions during the surface preparation of pre 1960's painted surfaces as they may contain harmful lead. For further information contact the Crown Customer Relations Team. When preparing all surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask. Material Safety Data Sheets for this and all other Crown Paints products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children or animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.



P O Box 37, Crown House, Hollins Road, Darwen, Lancashire, BB3 0BG

Tel: 01254 704951 Fax: 01254 870155

Email: info@crownpaint.co.uk

Website: www.crownpaint.co.uk